

2014 Porsche 911 Targa Models

Technical Data 911 Targa 4 911 Targa 4

| recillical Data | Fil Talga 4 | 311 Talga 43 |
|---------------------------------------|---|---|
| Engine | | |
| Engine layout | Rear engine | Rear engine |
| Engine type | 6-cylinder boxer engine | 6-cylinder boxer engine |
| Cylinders | 6 | 6 |
| Valves per cylinder | 4 | 4 |
| Construction | Aluminum block and heads | Aluminum block and heads |
| Fuel injection | Direct Fuel Injection (DFI), 140 bar | Direct Fuel Injection (DFI), 140 bar |
| Fuel | Premium | Premium |
| Displacement | 3.4 liter | 3.8 liter |
| Bore/Stroke | 91.0 mm / 77.5 mm | 102.0 mm / 77.5 mm |
| Maxmimum power output @ engine speed | 350 hp @ 7,400 rpm | 400 hp @ 7,400 rpm |
| Maximum torque @ engine speed | 287 lbft. @ 5,600 rpm | 325 lbft. @ 5,600 rpm |
| Electrical System | 12 volt, 2100 watt alternator, 70 Ah battery | 12 volt, 2100 watt alternator, 70 Ah battery |
| Maximum engine speed | 7,800 rpm | 7,800 rpm |
| Compression ratio | 12.5:1 | 12.5:1 |
| Power to weight ratio (lbs/hp) (PDK) | 9.7 (9.83) | 8.57 (8.68) |
| Output per liter | 102.9 hp/l | 105.3 hp/l |
| Lubrication | Integrated dry-sump | Integrated dry-sump |
| Engine Management | EMS SDI 9.1 | EMS SDI 9.1 |
| Drivetrain | All-wheel-drive, with electronically controlled, hydraulically actuated multi-plate center differential, locking rear differential, PTM | All-wheel-drive, with electronically controlled, hydraulically actuated multi-plate center differential, locking rear differential, PTM |
| Chassis & Suspension | | |
| Body | 2+2-seat, coupe, aluminum and steel composite unibody, aluminum doors and hood | 2+2-seat, cabriolet aluminum and steel composite unibody, aluminum doors and hood |
| Front Axle | Independent MacPherson strut with tranverse and longitudinal control arm, shock inside spring | Independent MacPherson strut with tranverse and longitudinal control arm, shock inside spring |
| Rear Axle | Independent multi-link suspension with shock inside spring | Independent multi-link suspension with shock inside spring |
| Steering System | Electro-mechanical power steering | Electro-mechanical power steering |
| Steering Ratio | 12.25:1 - 16.6:1 | 12.25:1 - 16.6:1 |
| Turning Circle | 36.4 ft. | 36.4 ft. |
| Brakes & Wheels | | |
| Caliper type | Fixed aluminum monobloc | Fixed aluminum monobloc |
| Rotor material | Steel, drilled and internally vented | Steel, drilled and internally vented |
| Caliper color | Black | Red |
| Number of pistons (front/rear) | 6/4 | 6 / 4 |
| Steel Rotor diameter (front/rear) mm | 330 / 330 | 340 / 330 |
| Steel Rotor thickness (front/rear) mm | 28 / 28 | 34 / 28 |
| PCCB rotor diameter (front/rear)mm | 350 / 350 (Opt.) | 350 / 350 (Opt.) |
| PCCB rotor thickness(front/rear)mm | 34/28 (Opt.) | 34/28 (Opt.) |
| Wheel type (standard) | Carrera Wheel | Carrera S Wheel |
| Wheels and tires front (standard) | 8.5J x 19 | 8.5J x 20 |
| | 235/40 ZR 19 | 245/35 ZR 20 |
| Wheels and tires rear (standard) | 11J x 19 | 11J x 20 |
| | 295/35 ZR 19 | 305/30 ZR 20 |



2014 Porsche 911 Targa Models

911 Targa 4 911 Targa 4S Technical Data

| Technical Data | 511 Taiga 4 | 911 Talga 40 |
|---|-----------------------------|-----------------------------|
| Transmission | | |
| Manual Transmission | 7-speed manual | 7-speed manual |
| PDK Transmission (Opt.) | 7-speed PDK | 7-speed PDK |
| Ratios (PDK in parentheses) | | |
| 1st | 3.91 (3.91) | 3.91 (3.91) |
| 2nd | 2.29 (2.29) | 2.29 (2.29) |
| 3rd | 1.55 (1.65) | 1.55 (1.65) |
| 4th | 1.30 (1.30) | 1.30 (1.30) |
| 5th | 1.08 (1.08) | 1.08 (1.08) |
| 6th | 0.88 (0.88) | 0.88 (0.88) |
| 7th | 0.71 (0.62) | 0.71 (0.62) |
| Reverse | 3.55 (3.55) | 3.55 (3.55) |
| Final Drive Ratio | 3.44:1 (3.44:1) | 3.44:1 (3.44:1) |
| Dimensions, Aerodynamics, & Weight | | |
| Length (inches) | 176.8 | 176.8 |
| Wheelbase (inches) | 96.4 | 96.4 |
| Width w/ mirrors (inches) | 77.8 | 77.8 |
| Width w/o mirrors (inches) | 72.9 | 72.9 |
| Height (inches) (PDK) | 51.1 | 50.8 (50.7) |
| Track width front (inches) | 60.3 | 60.3 |
| Track width rear (inches) | 61.4 | 61.4 |
| Drag coefficient (Cd) | 0.30 | 0.30 |
| Legroom* (inches) | TBD | TBD |
| Headroom (inches) | TBD | TBD |
| Cargo area volume (cuft.) seats down | 10 | 10 |
| Fuel tank capacity - refill volume (gal) | 17.9 | 17.9 |
| Curb weight (lbs) (PDK) | 3,395 (3,439) | 3,428 (3,472) |
| Gross Vehicle Weight (lbs) (PDK) | 4,244 (4,288) | 4,321 (4,365) |
| Performance | | |
| Top track speed (mph) | 175 | 183 |
| Top track speed (mph) (PDK) | 174 | 182 |
| Acceleration 0-60 (mph) | 5.0 | 4.6 |
| Acceleration 0-60 (mph) (PDK) | 5.0 (4.8 w/ Sport Chrono) | 4.4 (4.2 w/ Sport Chrono) |
| 1/4 mile from standing start (secs) | 13.3 | 12.9 |
| 1/4 mile from standing start (secs) (PDK) | 13.2 (12.9 w/ Sport Chrono) | 12.8 (12.5 w/ Sport Chrono) |
| Fuel Economy/Rating | | |
| Rating | TBD | TBD |
| City | TBD | TBD |
| Highway | TBD | TBD |
| Combined | TBD | TBD |
| | | |

^{*} Interior Length: Driver's Side: from depressed pedal to the hip point of seat